

suction cup ESS-40-SN

Part number: 189304

FESTO

easily interchangeable,



Data sheet

| Feature | Value |
|---|---|
| Min. workpiece radius | 230 mm |
| Nominal size | 3 mm |
| suction cup diameter | 40 mm |
| suction cup volume | 1.566 cm ³ |
| Position of connection | on top |
| Assembly position | Any |
| Correlation to suction-cup holder | Size 4 |
| Suction cup shape | round flat |
| Operating pressure | 0 ... 0.95 bar |
| Nominal operating pressure | -0.7 bar |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7::-] |
| Corrosion resistance classification CRC | 1 - Low corrosion stress |
| Food-safe | See Supplementary material information |
| Ambient temperature | -10 ... 70 °C |
| Retention force at nominal operating pressure | 69.6 N |
| Lateral force at nominal operating pressure | 60 N |
| Product weight | 16.3 g |
| Mounting type | Via vacuum port |
| Vacuum connection | M6 |
| Colour | Black |
| Shore hardness | 60 +/- 5 |
| Material of threaded plug | Wrought aluminium alloy, nickel-plated Nickel-plated brass Galvanised and chrome-plated steel |
| Materials note | Free of copper and PTFE Conforms to RoHS |
| Material suction cup | NBR |